



Highlights

2 to 12 poles

2 and 3 pole modules

Spacing 5.0 mm

Wire guard type

Wire entry vertical to PCB

Test jack on every clamping point

24 A with 2.5 mm² wire

Wire Sizes

Solid min 0.2 mm²

Solid max 2.5 mm²

Stranded (flexible) min 0.2 mm²

Stranded (flexible) max 2.5 mm²

Stranded with ferrule min 0.2 mm²

Stranded with ferrule max 2.5 mm²

Dimensions

Stripped length 6.0 mm

PCB hole diameter 1.3 mm

Materials

Clamp Brass

Wire guard Stainless Steel

Screw Steel

Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

Temperatures

Operating temperature -40 °C (without mech. load) - 105 °C

Store temperature -40 °C - 105 °C

Spacing 5.0 mm

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

GREY, RAL 7016

BLUE, RAL 5015

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

	cFUS			VDE	
UseGroup	B	C	D		
Rated voltage	300 V	-	300 V	250 V	
Rated current	20 A	-	10 A	24 A	
Rated wire size				min	max
- solid	AWG 22-12	-	AWG 22-12	0.5 mm ²	2.5 mm ²
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 22-12	-	AWG 22-12	0.5 mm ²	2.5 mm ²
Torque	0.45 Nm	-	0.45 Nm	0.50 Nm	
Screw size	M3	-	M3	M3	
Test voltage	1.60 kV	-	1.60 kV	2.0 kV	

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-5.0/5.08-LIGHT GREY	Art.-Nr. 500000000006
	Bridge, 3-pole, insulated, BRI/3-5.0/5.08-LIGHT GREY	Art.-Nr. 500000000007
	Bridge, 2-pole, BR/2-5.0/5.08-L7.0	Art.-Nr. 500000000008



Technical Data // AK100/..DS-5.0-H-GREY

PTR HARTMANN

A Phoenix Mecano Company

Spacing 5.0 mm

Order Data (Spacing 5.0 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	10.70	AK100/2DS-5.0-H-GREY	50100020150 G	250
3	15.70	AK100/3DS-5.0-H-GREY	50100030150 G	250
4	20.70	AK100/4DS-5.0-H-GREY	50100040150 G	250
5	25.70	AK100/5DS-5.0-H-GREY	50100050150 G	250
6	30.70	AK100/6DS-5.0-H-GREY	50100060150 F	200
7	35.70	AK100/7DS-5.0-H-GREY	50100070150 F	200
8	40.70	AK100/8DS-5.0-H-GREY	50100080150 E	100
9	45.70	AK100/9DS-5.0-H-GREY	50100090150 E	100
10	50.70	AK100/10DS-5.0-H-GREY	50100100150 E	100
11	55.70	AK100/11DS-5.0-H-GREY	50100110150 E	100
12	60.70	AK100/12DS-5.0-H-GREY	50100120150 E	100

Technical drawing

