



Spacers for LED

– universal mount for LED Ø 3 mm and 5 mm, self retaining

					
art. no.	B [mm]	dim. [mm] A	art. no.	B [mm]	dim. [mm] A
MAH 31	1.5	3.1	MAH 71	4.7	7.1
MAH 41		4.1	MAH 81		8.1
MAH 51		5.1	MAH 89		8.9
MAH 61		6.1	MAH 99		9.9
insulating body material:		MPPS, black			
temperature range:		-40°C...+240°C/ (260°C/5 s)			
class of inflammability:		UL 94 V-0			

					
art. no.	dim. [mm] A		art. no.	dim. [mm] A	
MAH 401	1		MAH 406	6	
MAH 402	2		MAH 407	7	
MAH 403	3		MAH 408	8	
MAH 404	4		MAH 409	9	
MAH 405	5		MAH 410	10	
insulating body material:		PVC Blend, black			
temperature range:		-40°C... +85°C			
class of inflammability:		UL 94 V-0			

Connector-sleeves → F 19 – 20
 LED-holders for front panel assembly → L 5
 Fourfold-LED-holders → L 8
 Horizontale Lichtleiter → L 10

LED-holders for PCB assembly → L 6 – 8
 Sockets for LED → F 5 – 6
 Light pipes for SMDs, vertical → L 9 – 10

A
B
C
D
E
F
G
H
I
K
L
M
N