


Optocoupler, Phototransistor Output, AC Input, Low Input Current

Features

- High Common-mode Interference Immunity
- Isolation Test Voltage, 5300 V_{RMS}
- Low Coupling Capacitance
- Good CTR Linearity Depending on Forward Current
- Low CTR Degradation
- High Collector-emitter Voltage, V_{CEO} = 55 V
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



i179080

Agency Approvals

- UL1577, File No. E52744 System Code J
- DIN EN 60747-5-2 (VDE0884)
DIN EN 60747-5-5 pending
Available with Option 1

Applications

Telecom
Industrial Controls
Battery Powered Equipment
Office Machines

Description

The SFH628A (DIP) and SFH6286 (SMD) feature a high current transfer ratio, low coupling capacitance and high isolation voltage. These couplers have a GaAs infrared emitting diode, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a plastic DIP-4 or SMD package.

The coupling devices are designed for signal transmission between two electrically separated circuits.

The couplers are end-stackable with 2.54 mm lead spacing.

Creepage and clearance distances of > 8.0 mm are achieved with option 6. This version complies with IEC 60950 (DIN VDE 0805) for reinforced insulation to an operation voltage of 400 V_{RMS} or DC.

Order Information

| Part | Remarks |
|---------------|---|
| SFH628A-2 | CTR 63 - 200 %, DIP-4 |
| SFH628A-3 | CTR 100 - 320 %, DIP-4 |
| SFH628A-4 | CTR 160 - 500 %, DIP-4 |
| SFH6286-2 | CTR 63 - 200 %, SMD-4 |
| SFH6286-3 | CTR 100 - 320 %, SMD-4 |
| SFH6286-4 | CTR 160 - 500 %, SMD-4 |
| SFH628A-2X006 | CTR 63 - 200 %, DIP-4 400 mil (option 6) |
| SFH628A-3X006 | CTR 100 - 320 %, DIP-4 400 mil (option 6) |
| SFH628A-3X007 | CTR 100 - 320 %, SMD-4 (option 7) |
| SFH628A-4X006 | CTR 160 - 500 %, DIP-4 400 mil (option 6) |

For additional information on the available options refer to Option Information.

Absolute Maximum Ratings

$T_{amb} = 25\text{ °C}$, unless otherwise specified

Stresses in excess of the absolute Maximum Ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute Maximum Rating for extended periods of the time can adversely affect reliability.

Input

| Parameter | Test condition | Symbol | Value | Unit |
|-----------------------|--------------------------|-----------|-----------|------|
| DC Forward current | | I_F | ± 50 | mA |
| Surge forward current | $t \leq 10\ \mu\text{s}$ | I_{FSM} | ± 2.5 | A |

Output

| Parameter | Test condition | Symbol | Value | Unit |
|---------------------------|---------------------------|------------|-------|------|
| Collector-emitter voltage | | V_{CE} | 55 | V |
| Emitter-collector voltage | | V_{EC} | 7.0 | V |
| Collector current | | I_C | 50 | mA |
| | $t_p \leq 1.0\ \text{ms}$ | I_C | 100 | mA |
| Power dissipation | | P_{diss} | 150 | mW |

Coupler

| Parameter | Test condition | Symbol | Value | Unit |
|--|--|-----------|----------------|--------------------|
| Isolation test voltage between emitter and detector, refer to Climate DIN 40046, part2, Nov.74 | | V_{ISO} | 5300 | V_{RMS} |
| Creepage distance | | | ≥ 7.0 | mm |
| Clearance | | | ≥ 7.0 | mm |
| Insulation thickness between emitter and detector | | | ≥ 0.4 | mm |
| Comparative tracking index per DIN IEC 112/VDEO 303, part 1 | | | 175 | |
| Isolation resistance | $V_{IO} = 500\ \text{V}, T_{amb} = 25\text{ °C}$ | R_{IO} | $\geq 10^{12}$ | Ω |
| | $V_{IO} = 500\ \text{V}, T_{amb} = 100\text{ °C}$ | R_{IO} | $\geq 10^{11}$ | Ω |
| Storage temperature range | | T_{stg} | - 55 to +150 | $^{\circ}\text{C}$ |
| Ambient temperature range | | T_{amb} | - 55 to +100 | $^{\circ}\text{C}$ |
| Junction temperature | | T_j | 100 | $^{\circ}\text{C}$ |
| Soldering temperature | max. 10 s. Dip Soldering distance to seating plane $\geq 1.5\ \text{mm}$ | T_{sld} | 260 | $^{\circ}\text{C}$ |



Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

Input

| Parameter | Test condition | Symbol | Min | Typ. | Max | Unit |
|--------------------|---|------------|-----|------|-----|------|
| Forward voltage | $I_F = 5.0\text{ mA}$ | V_F | | 1.1 | 1.5 | V |
| Capacitance | $V_R = 0\text{ V}$, $f = 1.0\text{ MHz}$ | C_O | | 45 | | pF |
| Thermal resistance | | R_{thja} | | 1070 | | K/W |

Output

| Parameter | Test condition | Symbol | Min | Typ. | Max | Unit |
|-----------------------------------|--|------------|-----|------|-----|------|
| Collector-emitter leakage current | $V_{CE} = 10\text{ V}$ | I_{CEO} | | 10 | 200 | nA |
| Collector-emitter capacitance | $V_{CE} = 5.0\text{ V}$, $f = 1.0\text{ MHz}$ | C_{CE} | | 7 | | pF |
| Thermal resistance | | R_{thja} | | 500 | | K/W |

Coupler


| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|--------------------------------------|--|------------------------|-------------|-----|------|-----|------|
| Collector-emitter saturation voltage | $I_F = \pm 1.0\text{ mA}$, $I_C = 0.5\text{ mA}$ | SFH628A-2 SFH6286-2 | V_{CEsat} | | 0.25 | 0.4 | V |
| | $I_F = \pm 1.0\text{ mA}$, $I_C = 0.8\text{ mA}$ | SFH628A-3 SFH6286-3 | V_{CEsat} | | 0.25 | 0.4 | V |
| | $I_F = \pm 1.0\text{ mA}$, $I_C = 1.25\text{ mA}$ | SFH628A-4 SFH6286-4 | V_{CEsat} | | 0.25 | 0.4 | V |

Current Transfer Ratio

| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|-----------|---|------------------------|--------|-----|------|-----|------|
| I_C/I_F | $I_F = \pm 1.0\text{ mA}$, $V_{CE} = 0.5\text{ V}$ | SFH628A-2 SFH6286-2 | CTR | 63 | | 200 | % |
| | $I_F = \pm 0.5\text{ mA}$, $V_{CE} = 1.5\text{ V}$ | SFH628A-2 SFH6286-2 | CTR | 32 | 100 | | % |
| | $I_F = \pm 1.0\text{ mA}$, $V_{CE} = 0.5\text{ V}$ | SFH628A-3 SFH6286-3 | CTR | 100 | | 320 | % |
| | $I_F = \pm 0.5\text{ mA}$, $V_{CE} = 1.5\text{ V}$ | SFH628A-3 SFH6286-3 | CTR | 50 | 160 | | % |
| | $I_F = \pm 1.0\text{ mA}$, $V_{CE} = 0.5\text{ V}$ | SFH628A-4 SFH6286-4 | CTR | 160 | | 500 | % |
| | $I_F = \pm 0.5\text{ mA}$, $V_{CE} = 1.5\text{ V}$ | SFH628A-4 SFH6286-4 | CTR | 80 | 250 | | % |


Switching Characteristics

| Parameter | Test condition | Symbol | Min | Typ. | Max | Unit |
|---------------|---|-----------|-----|------|-----|---------------|
| Turn-on time | $V_{CC} = 5.0\text{ V}$, $I_C = 2.0\text{ mA}$, $R_L = 100\ \Omega$ | t_{on} | | | 6.0 | μs |
| Rise time | $V_{CC} = 5.0\text{ V}$, $I_C = 2.0\text{ mA}$, $R_L = 100\ \Omega$ | t_r | | | 3.5 | μs |
| Turn-off time | $V_{CC} = 5.0\text{ V}$, $I_C = 2.0\text{ mA}$, $R_L = 100\ \Omega$ | t_{off} | | | 5.5 | μs |
| Fall time | $V_{CC} = 5.0\text{ V}$, $I_C = 2.0\text{ mA}$, $R_L = 100\ \Omega$ | t_f | | | 5.0 | μs |



isfh618a_11


Figure 1. Test Circuit



isfh618a_12


Figure 2. Test Circuit and Waveforms

Typical Characteristics ($T_{amb} = 25\text{ }^\circ\text{C}$ unless otherwise specified)



isfh618a_01

Figure 3. Current Transfer Ratio (typ.)



isfh618a_02

Figure 4. Current Transfer Ratio (typ.)




Figure 5. Diode Forward Voltage (typ.)




Figure 8. Output Characteristics




Figure 6. Diode Forward Voltage (typ.)




Figure 9. Permissible Forward Current Diode




Figure 7. Transistor Capacitance




Figure 10. Permissible Power Dissipation






Figure 11. Switching times (typ.)


Package Dimensions in Inches (mm)




Package Dimensions in Inches (mm)



Option 6



Option 7



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.