



GNSS Module



SIM68V

SIMCom presents a high performance and reliable GNSS module-SIM68V. This is a standalone L1 frequency GNSS module in a SMT type with MTK's high sensitivity navigation engine, which allows customer to achieve industry's high level sensitivity, accuracy, and Time-to-First-Fix (TTFF) with lower power consumption.

Smart Machine Smart Decision

Mechanical data

- Dimensions: 16*12.2*2.7mm
- Weight: 1g

Features

- Support GPS/GLONASS/Galileo/QZSS
- Support EASY™ self-generated orbit prediction
- Support EPO™ orbit prediction
- Support SBAS ranging (WAAS, EGNOS, GAGAN, MSAS)
- Jamming Removing supported
- Low-noise amplifier has been integrated

Interfaces

- Serial interfaces UART, SPI / I²C
- Digital I/O EINT0 input
Pulse-per-second (PPS)
- Protocols NMEA
PMTK

Support product

- SIM68 EVB KIT with USB V2.0 full speed interface

Performance data

- Receiver type 33tracking/99 acquisition-channel GNSS receiver
- Max. update rate 10Hz
- Sensitivity¹
 - Tracking: -167 dBm
 - Reacquisition: -157 dBm
 - Cold starts: -148 dBm
- Time-To-First-Fix²
 - Cold starts: 28 s
 - Warm start: 26 s
 - Hot starts: <1s
 - EPO Assist: 13s (CTTFF)
- Accuracy
 - Automatic Position³: 2.5m CEP
 - EPO 30days DATA: 1.99m
 - Speed⁴: 0.1m/s
- Operation temperature⁵: -40℃~+85℃

Electrical data

- Power supply 2.8V~4.3V
- Backup power 2.3V~4.6V
- Power consumption^{2,6}
 - Acquisition 34mA
 - Tracking 27mA
 - AlwaysLocate™ <200uA
- Antenna type Active and passive
- Antenna power External or internal VCC_RF

- 1.Demonstrated in lab
- 2.All SV @ -130 dBm, GPS&GLONASS mode
- 3.50% 24 hr static, -130dBm,GPS&GLONASS mode
- 4.50% @ 30m/s
- 5.When at -40℃~ -30℃,the sensitivity will be somewhat worse
6. @2.8V with a passive antenna

More about SIMCom SIM68V
Please contact:
Tel: 86-21-32523300
Fax: 86-21-32523301
Email: simcom@sim.com
Website: www.sim.com