



RECOMMEND P.C.BOARD HOLE LAYOUT

1. MATERIAL:

- 1.1 INSULATOR: PBT UL94-0
- 1.2 CONTACT: COPPER ALLOY

2. CHARACTERISTICS:

- 2.1 CURRENT RATING : 1.5A
- 2.2 CONTACT RESISTANCE: INITIAL:  $20m\Omega$  MAX
- 2.3 DIELECTRIC WITHSTANDING VOLTAGE : 500V
- 2.4 INSULATOR RESISTANCE: INITIAL:  $1000M\Omega$  MIN

3. OPERATING TEMP RANGE:  $-40^\circ\text{C}$  TO  $+105^\circ\text{C}$

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 $\pm 0.38$ .00 $\pm 0.25$ ANG. $\pm 5^\circ$	PART NAME 品名 2.54mm PIN HEADER DUAL ROW XX P STRAIGHT TYPE (C=6.0mm D=3.0mm )LOW LEAD
DWG. 製圖 Yumi	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C2200-XXBSXAS0R
DATE 制表日 2008/06/12	PAGE 張數 1 OF 1	REV. 版次 A	