

Series 730

SPECIFICATIONS

技術資料

Box Header



730-242-11

730-242-21

MATERIAL

- **Insulator:** PBT +30% Glass Fiber (UL 94 V-0)
- **Contact:** Brass
- **Contact Plated:** Gold over Nickel or Tin

ELECTRICAL

- **Current Rating:** 1A
- **Contact Resistance:** 10mΩMax. at DC 1A
- **Insulation Resistance:** 1000mΩMin. at DC 500V
- **Dielectric Strength:** AC 500V Per minute




MECHANICAL

- **Operating temperature:** -55°C to +105°C

FEATURES




- Box header body helps maximum packaging density.
- Available with wrap post tail header.
- Available in straight or right angle pins.

SERIES 730 (STRAIGHT)



Straight

SERIES 730 (RIGHT ANGLE)



Right Angle

No. of Pin	Dimension		
	A	B	C
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.85
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	67.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.65
64	88.88	86.68	78.74

Unit = mm

HOW TO ORDER 排序整理

7 3 0 - X X X - X X

Series No.
系列編號No. of Pin
針腳數目

Color

Pin Style

Plating

1	Grey	1	Straight	1	Gold Plated
2	Black	2	Right Angle	2	Tin Plated