




REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	JUN.10.02
B		MODIFY 49/98 DIM. A, B, C	NOV. 10' 03



Section A-A



Position	Dimension		
	A	B	C
3/6	14.22	10.36	5.08
4/8	16.76	12.90	7.62
6/12	21.84	17.98	12.70
8/16	26.92	23.06	17.78
10/20	32.00	28.14	22.86
12/24	37.08	33.22	27.94
13/26	39.62	35.76	30.48
14/28	42.16	38.30	33.02
15/30	44.70	40.84	35.56
16/32	47.24	43.38	38.10
17/34	49.78	45.92	40.64
18/36	52.32	48.46	43.18
19/38	54.86	51.00	45.72
20/40	57.40	53.54	48.26
22/44	62.48	68.62	53.34
24/48	67.56	63.70	58.42
25/50	70.10	66.24	60.96
30/60	82.80	78.94	73.66
31/62	85.34	81.48	76.20
32/64	87.88	84.02	78.74
35/70	95.50	91.64	86.36
36/72	98.04	94.18	88.90
40/80	108.20	104.34	99.06
43/86	115.82	111.96	106.68
49/98	138.68	134.82	129.54
50/100	133.60	129.74	124.46
54/108	143.76	139.90	134.62
60/120	159.00	155.14	149.86

FEATURE:
 INSULATOR
 Glass-Filled P.B.T. is 94V-0 rated
 CONTACT
 Phosphor Bronze selective gold plating
 over nicket

SPECIFICATION
 Current Rating: 3 amperes
 Contact Resistance: 20 miniohms max.
 Operation Temperature: -55°C to 105°C
 Voltage rating: 800VAC 1 minute
 Insulation Resistance: 5000 megaohms min
 Insertion Force: 412 grams max. per pair
 Withdrawal Force: 32 grams min. per pair

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJECTION		GOLD-TEK ELECTRIC CO., LTD.	
LINEAR	ANGLE	UNITS		TITLE	PART NO.
X. ±	X° ±	MM	EDGE CARD 180°	ECA**ST2	
.X ± 0.38	.X° ±		W/O EARS	CAD NO. I133	SHEET
.XX ± 0.25	.XX° ±	SCALE	CPART NO	F:\Drw\SOC\SOC-0058	1 OF 1
.XXX ±	.XXX° ±	SIZE		圖面編號:GTKSD0663-B(1)	
APPD		A4			
CHKD					
DRAW	Z.	NOV. 10' 2003			