



SPECIFICATION FOR LED LAMP

PART NO. : LT6385-41-940

2.9MM ROUND INFRARED LAMP

Prepared by: 包正敏

Checked by: 周道焰

Approved by: 王方波

LEDTECH ELECTRONICS CORPORATION

*NANYA ROAD, MUGANG ZHAOQING CITY
GUANGDONG CHINA.*

TEL: 86-758-2875541, 2870651, 2877464, 2876185, 2877017

FAX: 86-758-2878014

Http://www.ledtech.com.tw



2.9MM ROUND INFRARED LAMP

PART NO. : LT6385-41-940

Page : 1/4


Features

- * High radiant power
- * Reliable and rugged
- * Lower degradation
- * IC Compatible

Description

The Infrared lamps are made with AlGaAs/GaAs chips and blue clear epoxy resin.

Package Dimensions



Notes:

- 1.All dimensions are in millimeters.
- 2.Tolerance is ± 0.25 mm unless otherwise noted.

Part No.	Led Chip		Lens Color
	Material	Emitting Color	
LT6385-41-940	AlGaAs/GaAs	Infrared	Blue Clear



2.9MM ROUND INFRARED LAMP

PART NO. : LT6385-41-940

Page : 2/4

Absolute Maximum Ratings at Ta=25°C :

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	75	mW
Reverse Voltage	Vr	5	V
D.C. Forward Current	If	50	mA
Peak Current (1/10 Duty Cycle , 0.1 ms Pulse Width)	If(Peak)	1	A
Operating Temperature Range	Topr	-25 to +85	°C
Storage Temperature Range	Tstg	-40 to +100	°C
Lead Soldering Temp.(1.6mm from body) for 5 seconds		260	°C

Electrical and Optical Characteristics :

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Rad iant Intensity	Ee	If=100mA	8.0	13.0		mw
Forward Voltage	Vf	If=20mA		1.2	1.5	V
		If=100mA		1.3	1.7	V
Peak Wavelength	λP	If=100mA		940		nm
Dominant Wavelength	λD	-----				nm
Reverse Current	Ir	Vr=5V			100	μA
Viewing Angle	$2 \theta 1/2$	If=20mA		30		deg
Spectrum Line Halfwidth	$\Delta \lambda$	If=20mA		50		nm




2.9MM ROUND INFRARED LAMP


PART NO. : LT6385-41-940

Page : 3/4


Typical Electrical / Optical Characteristics Curves :




FORWARD CURRENT VS. APPLIED VOLTAGE



FORWARD CURRENT VS. LUMINOUS INTENSITY



AMBIENT TEMPERATURE VS. FORWARD CURRENT



RADIATION DIAGRAM



2.9MM ROUND INFRARED LAMP

PART NO. : LT6385-41-940

Page : 4/4

Reliability Test Method :

Test Item	Test Condition	Duration Time
Operation Life	If=20mA / Ta=25℃	168hrs
Storage at High Temperature	Ta=100℃	168hrs
Storage at Low Temperature	Ta=-40℃	168hrs
Storage at High Temperature/High Humidity	Ta=85℃ /RH=85%	168hrs
Operating at High Temperature	Ta=85℃ / If=20mA	168hrs
Operating at Low Temperature	Ta=25℃ / If=20mA	168hrs
Thermal Shock	Ta/T=100℃/30min~ -40℃/30min	10 cycles
Solderability	Tsol=230℃	5 sec

Criteria for Judging The Damage:

Item	Symbol	Test Condition	Criteria for Judgment	
			Min.	Max.
Forward Voltage	Vf	If=20mA If=100mA	-----	Initial Data $\times 1.1$
Reverse Current	Ir	Vr=5V	-----	100 μ A
Luminous Intensity	Ee	If=20mA	Initial Data $\times 0.8$	-----