



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: PA 66
 FLAMABILITY RATING: UL94-V0
 COLOR: WHITE
 CONTACT MATERIAL: COPPER ALLOY
 CONTACT TYPE: STAMPED
 CONTACT PLATING: TIN
 QUALITY CLASS: 25 MATING CYCLES
 PITCH: 2.00MM

ENVIRONMENTAL
 OPERATING TEMPERATURE: -25 UP TO 85°C
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 CURRENT RATING: 2A
 WORKING VOLTAGE: 125V AC
 INSULATOR RESISTANCE: >1000 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 800V AC/MN
 CONTACT RESISTANCE: 20 mOHM MAX

SOLDERING
 WAVE PROCESS ONLY

PACKAGING
 BAG

DIMENSION
 A = 2.00 x (NB PIN - 1)
 B = 2.00 x (NB PIN - 1) + 4.00
 C = 2.00 x (NB PIN - 1) + 3.00

PCB LAYOUT - COMPONENT VIEW

G				PROJECTION:	GENERAL TOLERANCE		DESCRIPTION: 2.00 MALE HORIZONTAL SHROUDED HEADER	SIZE A4
F					.X = +/- 0.2			
E					.XX = +/- 0.15			
D								
C				APPROVAL: RJ	UNIT: MM	DESCRIPTION: 2.00 MALE HORIZONTAL SHROUDED HEADER		SIZE A4
B					SCALE:	WERI PART NO: 620 0xx 117 22		
A	07-NOV-08	PDF	JP		SHEET: 1/1			
REV	DATE	FILE	BY		DRAW:			