

F3136 = Product group; Product group discount F 31 3_

IDC Connectors For Flat Cables Pitch: 2,54mm Series: LPV_T

New Products

Features

- RoHS compliant

Technical Specifications

Insulation Shell:PBT, Glass-filled, UL94V-0, Grey
 Contact Material:Brass
 Contact Surface:Tin over Nickel
 Rated Current:1A
 Test Voltage:500V AC
 Insulation Resistance (500V):1000MΩ
 Temperature Range:-40...+105°C

Dimensions

Part Nr.	Nr. of Poles	A [mm]	B [mm]
LPV10T	10	18,10	10,16
LPV14T	14	23,18	15,24
LPV16T	16	25,72	17,78
LPV20T	20	30,80	22,86
LPV26T	26	38,42	30,48
LPV34T	34	48,58	40,64
LPV40T	40	56,20	48,26
LPV50T	50	68,90	60,96

Note

For suitable flat cables, please see product groups G1833 and G1837.

For suitable IDC crimping fixtures MWZ215D, please see product group T4651 in our red "Components and Devices" catalogue.

Terms of Delivery

Minimum order quantity: 1 PKU = 10 pieces

Manufacturer: Various

Part Nr.	Part description	PU	10 up.	50 up.	200 up.
LPV10T	! IDC PC-Connector 10-Pole	H	26,05	17,85	13,75
LPV14T	! IDC PC-Connector 14-Pole	H	26,05	17,85	13,75
LPV16T	! IDC PC-Connector 16-Pole	H	27,80	19,00	14,60
LPV20T	! IDC PC-Connector 20-Pole	H	29,20	20,00	15,40
LPV26T	! IDC PC-Connector 26-Pole	H	33,00	22,60	17,40
LPV34T	! IDC PC-Connector 34-Pole	H	34,55	23,65	18,20
LPV40T	! IDC PC-Connector 40-Pole	H	38,05	26,05	20,05
LPV50T	! IDC PC-Connector 50-Pole	H	49,40	33,80	26,00

