


## Device Selection Guide


Part Number EOS-	Luminous Intensity $I_v(\text{mcd}) @ I_F = 150\text{mA}$		Viewing Angle $2\theta_{1/2}$	Dominant Wavelength $\lambda_D(\text{nm}) @ I_F = 150\text{mA}$	Forward Voltage $V_F(\text{V}) @ I_F = 150\text{mA}$		$I_R(\mu\text{A}) @ V_R = 5\text{V}$
	Min.	Typ.	Typ.	Typ.	Typ.	Max.	Max.
EOS-9AYSCR0-KL	3550	4500	120°	589	2.75	3.05	10

BIN #	5Y	4Z		
Intensity (mcd) @ $I_F = 150\text{mA}$	3550-4500	4500-5600		

## Package Dimensions



## Beam Pattern



**Note:**

- All dimensions are in millimeter.
- Tolerance is  $\pm 0.20\text{mm}$  unless otherwise note.
- Specifications are subject to be changed without notice.

## Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Parameter	Symbol	Maximum Value	USER---APPROVED
Average Forward Current	$I_F$	150mA	
Peak Forward Current <sup>[a]</sup>	$I_{\text{peak}}$	100mA	
Reverse Voltage	$V_R$	5V	
Power Dissipation	$P_D$	457.5mW	
Operating Temperature Range	$T_{\text{OPR}}$	-40°C ~ + 85°C	
Storage Temperature Range	$T_{\text{STO}}$	-40°C ~ + 100°C	
Lead Soldering Temperature	$T_{\text{SOL}}$	260°C / 5 seconds	

Notes: [a]  $t_p \leq 10 \mu\text{s}$ , Duty Cycle = 0.005

### Headquarters

5F, No. 1, Creation Road II, Hsinchu Science Park,  
Hsinchu, Taiwan 300, R.O.C.  
Tel : 886-3-5679000 Fax : 886-3-5679999  
<http://www.eoi.com.tw> E-mail : [Service@eoi.com.tw](mailto:Service@eoi.com.tw)

### U.S. Office

1400 W. Lambert Road, Suite B,  
Brea, CA92821, U.S.A  
Tel : 1-562-694-1246 Fax : 1-562-691-3087  
<http://www.eoi-us.com> E-mail : [Sales@eoius.com](mailto:Sales@eoius.com)

