

G1433 = Product group; Product group discount G 14 3_

KLASING PVC Control Cables

Twisted, Shielded

Cross-Section: 0,14mm²

Colour: Grey

Series: LIYCY

Construction

Screening, Cu Plaited, Tinned:85%
Conductor Insulation:.....PVC Y1 2
Conductor Colours:.....DIN 47 100
Conductor Composition:18x0,10mm
Outer Jacket:PVC YM 2
Colour:Grey (RAL 7032)
Flammability:Flame Resistant IEC332.1

Technical Specifications

Rated Voltage:.....300V
Test Voltage:.....>1,5kV
Temperature Range Moving:-10...+70°C
Temperature Range Stationary:.....-30...+80°C
Insulation Resistance, Min.:.....20MΩxkm
Conductor Resistance, Max.:135Ω/km

Part Nr.	Cross-Section [mm ²]	OuterØ [mm]
LIYCY0414	4x0,14	4,00 ±0,15
LIYCY0614	6x0,14	4,80 ±0,15
LIYCY0814	8x0,14	5,10 ±0,20
LIYCY0914	9x0,14	5,40 ±0,20
LIYCY1014	10x0,14	5,80 ±0,20
LIYCY1514	15x0,14	6,50 ±0,20
LIYCY2514	25x0,14	8,20 ±0,25

Terms of Delivery

Minimum order quantity: 1 PKU = 100m ring

Manufacturer: Klasing

<http://www.klasing-kabel.de>

Part Nr.	Part description
LIYCY0414	Control Cable 4x0,14mm ² Grey
LIYCY0614	Control Cable 6x,014mm ² Grey
LIYCY0814	Control Cable 8x0,14mm ² Grey
LIYCY0914	Control Cable 9x0,14mm ² Grey
LIYCY1014	Control Cable 10x0,14mm ² Grey
LIYCY1514	Control Cable 15x0,14mm ² Grey
LIYCY2514	Control Cable 25x0,14mm ² Grey

