



LEDTECH ELECTRONICS CORP.

: NANYA ROAD,MUGANG ZHAOQING
: CITY GUANGDONG CHINA.
: TEL:86-758-2875541,2870651,2877464,2876185,2877017
: FAX:86-758-2878014
: [Http://www.ledtech.com.tw](http://www.ledtech.com.tw)

SPECIFICATION

PART NO. : LT64B1-81-SBE3

4.8MM ROUND LED LAMP

Approved by	Checked by	Prepared by
<i>San</i>	<i>Spring</i>	<i>Bao Min</i>



**4.8MM ROUND LED LAMP
PART NO. : LT64B1-81-SBE3**


Features

- * High intensity
- * Reliable and rugged
- * Low current requirement
- * IC compatible

Description

The Blue lamp are made with InGaN chip and Blue diffused epoxy resin.

Package Dimensions



Notes:

- 1.All dimensions are in millimeters.
- 2.Tolerance is ± 0.25 mm unless otherwise noted.

Part No.	Led Chip		Lens Color
	Material	Emitting Color	
LT64B1-81-SBE3	InGaN	Blue	Blue diffused



4.8MM ROUND LED LAMP
PART NO. : LT64B1-81-SBE3

Absolute Maximum Ratings at Ta=25 :

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	80	mW
Reverse Voltage	Vr	5	V
D.C. Forward Current	If	20	mA
Peak Current (1/10 Duty Cycle , 0.1 ms Pulse Width)	If(Peak)	100	mA
Operating Temperature Range	Topr	-25 to +85	
Storage Temperature Range	Tstg	-40 to +100	
Lead Soldering Temp.(1.6mm from body) for 5 seconds		260	
Electrostatic discharge (ESD)		300	V


Electrical and Optical Characteristics :

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Intensity	Iv	If=20mA	100	180		mcd
Forward Voltage	Vf	If=20mA		3.2	4.0	V
Peak Wavelength	P	If=20mA		468		nm
Dominant Wavelength	D	If=20mA		470		nm
Reverse Current	Ir	Vr=5V			50	μ A
Viewing Angle	2 1/2	If=20mA		38		deg
Spectrum Line Halfwidth		If=20mA		26		nm




**4.8MM ROUND LED LAMP
PART NO. : LT64B1-81-SBE3**


Typical Electrical / Optical Characteristics Curves :




FORWARD CURRENT VS. APPLIED VOLTAGE



FORWARD CURRENT VS. LUMINOUS INTENSITY



AMBIENT TEMPERATURE VS. FORWARD CURRENT



RADIATION DIAGRAM



**4.8MM ROUND LED LAMP
PART NO. : LT64B1-81-SBE3**

Reliability Test Method :

Test Item	Test Condition	Duration Time
Operation Life	If=20mA / Ta=25	168hrs
Storage at High Temperature	Ta=100	168hrs
Storage at Low Temperature	Ta=-40	168hrs
Storage at High Temperature/High Humidity	Ta=85 /RH=85 %	168hrs
Operating at High Temperature	Ta=85 / If=20mA	168hrs
Operating at Low Temperature	Ta=-25 / If=20mA	168hrs
Thermal Shock	Ta/T=100 /30min~ -40 /30min	10 cycles
Solderability	Tsol=230	5 sec

Criteria for Judging The Damage:

Item	Symbol	Test Condition	Criteria for Judgment	
			Min.	Max.
Forward Voltage	Vf	If=20mA	-----	Initial Data x1.1
Reverse Current	Ir	Vr=5V	-----	50 μ A
Luminous Intensity	Iv	If=20mA	Initial Data x0.8	-----




**4.8MM ROUND LED LAMP
PART NO. : LT64B1-81-SBE3**

ENCASED TYPE


PLASTIC PACKAGE
QUANTITY: 200 PCS

LEDTECH ELECTRONICS CORP.					
PART NO :LTXXXX-XX					
Q'TY	:	PCS			
LOT NO	:	XXXXXXXXXX			
DATE	:				
BIN CODE:					



INNER BOX
QUANTITY: 40 PACKETS
TOTAL: 8,000 PCS

PART NO.	LXXXXX-XX-XX				
LOT NO.	XXXXXXXXXX				
BIN CODE	Xx X	Xx X	Xx X	Xx X	TOTAL
QUANTITY	PCS	PCS	PCS	PCS	PCS
DATE	XXXX . XX . XX				



OUTER CARTON
QUANTITY: 4 BOX
TOTAL: 32,000 PCS

C/T NO. 箱 號	XX
PART NO. 料 號	LXXXXX-XX-XX
QUANTITY 數 量	PCS
N.W. 淨 重	KGS
G.W. 毛 重	KGS
REMARK 備 註	

