

F4533 = Product group; Product group discount F 45 3_

HD D-Sub Sockets

Snap-In, Angled

Contacts: Stamped

Series: HDBL_WSI

Technical Specifications

Insulating Shell:.....PBT, +30% Glass-filled, UL94V-0
Contacts:.....Phosphor-Bronze or Brass
Contact Surface:.....Flash Gold Over Nickel
Soldered Side:.....Tin Over Nickel
Housing Frame:.....Steel, Tin-plated
Operating Current:5A
Dielectric Strength (For 1 Min.):500V
Insulation Resistance:1000 MΩ at 500V DC
Temperature Range:-55...+105°C

Dimensions

Part Nr.	Nr. of Poles	F	A	G
		[mm]	[mm]	[mm]
HDBL15WSI	15	30,81	24,99	16,33
HDBL44WSI	44	53,04	47,04	38,38

Note

- You will find adapter screw bolts with thread UNC4-40 in this catalogue at product group G8285.

Terms of Delivery

Minimum order quantity: 1 PKU = 10 pieces

HDBL44WSI: 1PKU = 5 pieces

Manufacturer: Various

Part Nr.	Part description
HDBL15WSI	HD D-Sub-Socket 15-Pole Solder Pin
HDBL44WSI	HD D-Sub-Socket 44-Pole Solder Pin

