



SPECIFICATION FOR COTCO LED LAMP

Document No: SPE/LC503TPG1-30H-A1
Model No : LC503TPG1-30H-A1
Rev. No: 01
Date: 2005-02-23


Description:

30 Degree 5mm LED Lamp in Pure Green Color
with Water Transparent Lens and No Stopper

Dice Material: InGaN

Confirmed
by Customer: _____

Date: _____



Applications:

- Advertising Signs
- Indicators
- LCD Back Light
- Moving Message Sign

Absolute Maximum Ratings at Ta = 25°C


Items	Symbol	Absolute maximum Rating	Unit
Forward Current	I_F	25	mA
Peak Forward Current*	I_{FP}	100	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	100	mW
Operation Temperature	T_{opr}	-40 ~ +95	°C
Storage Temperature	T_{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T_{sol}	Max.260°C for 3 sec Max. (3mm from the base of the epoxy bulb)	

*pulse width $\leq 0.1\text{msec}$ duty $\leq 1/10$

Typical Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F = 20\text{mA}$	---	3.4	4.0	V
Forward Voltage	V_F	$I_F = 1.0\mu\text{A}$	1.7	---	2.5	V
Reverse Current	I_R	$V_R = 5\text{V}$	---	---	100	μA
Dominant Wavelength	λ_D	$I_F = 20\text{mA}$	520	527	535	nm
Luminous Intensity	I_v	$I_F = 20\text{mA}$	4180	7500	---	mcd
50% Power Angle	$2\theta_{\frac{1}{2}H-H}$	$I_F = 20\text{mA}$	---	30	---	deg

Dimension Drawing




Standard bins for LC503TPG1-30H-A1 ($I_F = 20mA$):

Lamps are sorted to Luminous Intensity – I_V , V_F & Dominant Wavelength – λ_D bins shown.

Orders for LC503TPG1-30H-A1 may be filled with any or all bins contained as below.

All Luminous Intensity – I_V , V_F & Dominant Wavelength – λ_D values shown and specified are at $I_F = 20mA$.

* **X+**



* X+ indicates Luminous Intensity is at X bin or above.







Forward Voltage (V_F)

Rank	V6	V7	V8	V9	V10	V11	V12
Voltage	2.6-2.8V	2.8-3.0V	3.0-3.2V	3.2-3.4V	3.4-3.6V	3.6-3.8V	3.8-4.0V

Important Notes:

- 1) All ranks will be included per delivery; rank ratio will be based on the Dices distribution.
- 2) Pb content <1000PPM.
- 3) Tolerance of measurement of luminous intensity is $\pm 15\%$.
- 4) Tolerance of measurement of dominant wavelength is $\pm 1nm$.
- 5) Tolerance of measurement of V_f is $\pm 0.05 V$.
- 6) Packaging methods are available for selection, Please refer to PACKAGING STANDARD.
- 7) Please refer to LED LAMP RELIABILITY TEST STANDARD for reliability test conditions.
- 8) Please refer to APPLICATION NOTES for Application.

Graphs



Items	Signatures	Date
Prepared by	LiuZM	2005-02-23
Checked by	Aldosin	2005-02-23
Approved by	David	2005-02-23
ECN#	ECN-H20050055	

Revision History		
Rev. No	Date	Change Description

Data is subject to change without prior notice; please refer to COTCO Website for the latest version.

Copyright@2002 Cotco International Ltd.