



LEDTECH ELECTRONICS CORP.

NANYA ROAD, MUGANG ZHAOQING
CITY GUANGDONG CHINA.

TEL: 86-758-2875541, 2870651, 2877464, 2876185, 2877017

FAX: 86-758-2878014

Http://www.ledtech.com.tw

SPECIFICATION

PART NO. : LT1831-81-UBC1

5.0MM ROUND LED LAMP

Approved by	Checked by	Prepared by
<i>San</i>	<i>Spring</i>	<i>Bao Min</i>




**5.0MM ROUND LED LAMP
PART NO. : LT1831-81-UBC1**

Features

- * High intensity
- * Reliable and rugged
- * Low current requirement
- * IC compatible

Package Dimensions



Description

The Yellow lamp are made with AlGaInP/GaAs chip and yellow diffused epoxy resin.

Notes:

- 1.All dimensions are in millimeters.
- 2.Tolerance is ± 0.25 mm unless otherwise noted.

Part No.	Led Chip		Lens Color
	Material	Emitting Color	
LT1831-81-UBC1	AlGaInP/GaAs	Yellow	Yellow diffused



5.0MM ROUND LED LAMP
PART NO. : LT1831-81-UBC1

Absolute Maximum Ratings at Ta=25 :

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	72	mW
Reverse Voltage	Vr	4	V
D.C. Forward Current	If	30	mA
Peak Current (1/10 Duty Cycle , 0.1 ms Pulse Width)	If(Peak)	100	mA
Operating Temperature Range	Topr	-25 to +85	
Storage Temperature Range	Tstg	-40 to +100	
Lead Soldering Temp.(1.6mm from body) for 5 seconds		260	


Electrical and Optical Characteristics :

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Intensity	Iv	If=20mA	450	800		mcd
Forward Voltage	Vf	If=20mA		1.9	2.4	V
Peak Wavelength	P	If=20mA		589		nm
Dominant Wavelength	D	If=20mA		591		nm
Reverse Current	Ir	Vr=4V			100	μ A
Viewing Angle	2 1/2	If=20mA		32		deg
Spectrum Line Halfwidth		If=20mA		15		nm




**5.0MM ROUND LED LAMP
PART NO. : LT1831-81-UBC1**


Typical Electrical / Optical Characteristics Curves :




FORWARD CURRENT VS. APPLIED VOLTAGE



FORWARD CURRENT VS. LUMINOUS INTENSITY



AMBIENT TEMPERATURE VS. FORWARD CURRENT



RADIATION DIAGRAM



**5.0MM ROUND LED LAMP
PART NO. : LT1831-81-UBC1**

Page : 4/5

Reliability Test Method :

Test Item	Test Condition	Duration Time
Operation Life	If=20mA / Ta=25	168hrs
Storage at High Temperature	Ta=100	168hrs
Storage at Low Temperature	Ta=-40	168hrs
Storage at High Temperature/High Humidity	Ta=85 /RH=85 %	168hrs
Operating at High Temperature	Ta=85 / If=20mA	168hrs
Operating at Low Temperature	Ta=-25 / If=20mA	168hrs
Thermal Shock	Ta/T=100 /30min~ -40 /30min	10 cycles
Solderability	Tsol=230	5 sec

Criteria for Judging The Damage:

Item	Symbol	Test Condition	Criteria for Judgment	
			Min.	Max.
Forward Voltage	Vf	If=20mA	-----	Initial Data x1.1
Reverse Current	Ir	Vr=4V	-----	100 μ A
Luminous Intensity	Iv	If=20mA	Initial Data x0.8	-----




**5.0MM ROUND LED LAMP
PART NO. : LT1831-81-UBC1**

ENCASED TYPE


PLASTIC PACKAGE
QUANTITY: 1,000 PCS

LEDTECH ELECTRONICS CORP.	
PART NO :LTXXXX-XX	
QTY	: PCS
LOT NO	:XXXXXXXXXX
DATE	:
BIN CODE:	



INNER BOX
QUANTITY: 10 PACKETS
TOTAL: 10,000 PCS

PART NO.	LXXXXX-XX-XX				
LOT NO.	XXXXXXXXXX				
BIN CODE	Xx X	Xx X	Xx X	Xx X	TOTAL
QUANTITY	PCS	PCS	PCS	PCS	PCS
DATE	XXXX , XX , XX				



OUTER CARTON
QUANTITY: 4 BOX
TOTAL: 40,000 PCS

C/T NO. 箱 號	XX
PART NO. 料 號	LXXXXX-XX-XX
QUANTITY 數 量	PCS
N.W. 淨 重	KGS
G.V. 毛 重	KGS
REMARK 備 註	

