

TOSHIBA Bipolar Linear Integrated Circuit Silicon Monolithic

## TA79L005P, TA79L006P, TA79L008P, TA79L009P, TA79L010P, TA79L012P, TA79L015P, TA79L018P, TA79L020P, TA79L024P



-5 V, -6 V, -8 V, -9 V, -10 V, -12 V, -15 V, -18 V, -20 V, -24 V

Three-Terminal Negative Voltage Regulators

### Features


- Best suited to a power supply for TTL and C<sup>2</sup>MOS.
- Built-in overcurrent protective circuit.
- Built-in thermal protective circuit.
- Maximum output current of 150 mA ( $T_j = 25^\circ\text{C}$ ).
- Packaged in TO-92MOD.

### Pin Assignment




Weight: 0.36 g (Typ.)

### Marking



## Equivalent Circuit



## Absolute Maximum Ratings (Ta = 25°C)

| Characteristics       |             | Symbol               | Rating  | Unit |
|-----------------------|-------------|----------------------|---------|------|
| Input voltage         | TA79L005P   | V <sub>IN</sub>      | -35     | V    |
|                       | TA79L006P   |                      |         |      |
|                       | TA79L008P   |                      |         |      |
|                       | TA79L009P   |                      |         |      |
|                       | TA79L010P   |                      |         |      |
|                       | TA79L012P   |                      |         |      |
|                       | TA79L015P   |                      |         |      |
|                       | TA79L018P   |                      |         |      |
|                       | TA79L020P   |                      | -40     |      |
|                       | TA79L024P   |                      |         |      |
| Power dissipation     | (Ta = 25°C) | P <sub>D</sub>       | 800     | mW   |
| Operating temperature |             | T <sub>opr</sub>     | -30~85  | °C   |
| Storage temperature   |             | T <sub>stg</sub>     | -55~150 | °C   |
| Junction temperature  |             | T <sub>j</sub>       | 150     | °C   |
| Thermal resistance    |             | R <sub>th(j-a)</sub> | 156     | °C/W |

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/Derating Concept and Methods) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

**TA79L005P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -10\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                    | Test Circuit | Test Condition                                                                                                             | Min   | Typ. | Max   | Unit                 |
|---------------------------------------------------|---------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------|-------|------|-------|----------------------|
| Output voltage                                    | $V_{OUT}$                 | 1            | $T_j = 25^\circ\text{C}$                                                                                                   | -5.2  | -5.0 | -4.8  | V                    |
| Line regulation                                   | Reg.line                  | 1            | $T_j = 25^\circ\text{C}$ $-20\text{ V} \leq V_{IN} \leq -7.0\text{ V}$                                                     | —     | 55   | 150   | mV                   |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $-20\text{ V} \leq V_{IN} \leq -8.0\text{ V}$                                                     | —     | 45   | 100   |                      |
| Load regulation                                   | Reg.load                  | 1            | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 100\text{ mA}$                                                   | —     | 11   | 60    | mV                   |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$                                                    | —     | 5.0  | 30    |                      |
| Output voltage                                    | $V_{OUT}$                 | 1            | $T_j = 25^\circ\text{C}$ $-20\text{ V} \leq V_{IN} \leq -7.0\text{ V}$ ,<br>$1.0\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$ | -5.25 | —    | -4.75 | V                    |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 70\text{ mA}$                                                    | -5.25 | —    | -4.75 |                      |
| Quiescent current                                 | $I_B$                     | 1            | $T_j = 25^\circ\text{C}$                                                                                                   | —     | 3.1  | 6.0   | mA                   |
|                                                   |                           |              | $T_j = 125^\circ\text{C}$                                                                                                  | —     | —    | 5.5   |                      |
| Quiescent current change                          | $\Delta I_{BI}$           | 1            | $T_j = 25^\circ\text{C}$ $-20\text{ V} \leq V_{IN} \leq -8.0\text{ V}$                                                     | —     | —    | 1.5   | mA                   |
|                                                   | $\Delta I_{BO}$           | 1            |                                                                                                                            | —     | —    | 0.1   |                      |
| Output noise voltage                              | $V_{NO}$                  | 2            | $T_a = 25^\circ\text{C}$ , $10\text{ Hz} \leq f \leq 100\text{ kHz}$                                                       | —     | 40   | —     | $\mu\text{V}_{rms}$  |
| Long term stability                               | $\Delta V_{OUT}/\Delta t$ | 1            | —                                                                                                                          | —     | 12   | —     | mV/kh                |
| Ripple rejection ratio                            | R.R.                      | 3            | $-18\text{ V} \leq V_{IN} \leq -8.0\text{ V}$ ,<br>$T_j = 25^\circ\text{C}$ , $f = 120\text{ Hz}$                          | 41    | 49   | —     | dB                   |
| Dropout voltage                                   | $V_D$                     | 1            | $T_j = 25^\circ\text{C}$                                                                                                   | —     | 1.7  | —     | V                    |
| Average temperature coefficient of output voltage | $T_{CVO}$                 | 1            | $I_{OUT} = 5\text{ mA}$                                                                                                    | —     | 0.6  | —     | mV/ $^\circ\text{C}$ |

**TA79L006P**
**Electrical Characteristics**

(Unless otherwise specified,  $V_{IN} = -11\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                         |                                                                        | Min   | Typ. | Max   | Unit              |
|---------------------------------------------------|-----------------------|--------------|------------------------------------------------------------------------|------------------------------------------------------------------------|-------|------|-------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                  |                                                                        | -6.24 | -6.0 | -5.76 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                  | -21 V ≤ V <sub>IN</sub> ≤ -8.1 V                                       | —     | 50   | 150   | mV                |
|                                                   |                       |              |                                                                        | -21 V ≤ V <sub>IN</sub> ≤ -9.0 V                                       | —     | 45   | 110   |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                  | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                     | —     | 12   | 70    | mV                |
|                                                   |                       |              |                                                                        | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                      | —     | 5.5  | 35    |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                  | -21 V ≤ V <sub>IN</sub> ≤ -8.1 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -6.3  | —    | -5.7  | V                 |
|                                                   |                       |              |                                                                        | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                      | -6.3  | —    | -5.7  |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                  |                                                                        | —     | 3.1  | 6.0   | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                 |                                                                        | —     | —    | 5.5   |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                  | -21 V ≤ V <sub>IN</sub> ≤ -9.0 V                                       | —     | —    | 1.5   | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                        | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                      | —     | —    | 0.1   |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                             |                                                                        | —     | 40   | —     | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                      |                                                                        | —     | 14   | —     | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -19 V ≤ V <sub>IN</sub> ≤ -9.0 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                        | 39    | 47   | —     | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                  |                                                                        | —     | 1.7  | —     | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                                |                                                                        | —     | 0.7  | —     | mV/°C             |

**TA79L008P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -14\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                         | Min  | Typ. | Max  | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|------|------|------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | -8.3 | -8.0 | -7.7 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                 | -23 V ≤ V <sub>IN</sub> ≤ -10.5 V                                       | —    | 20   | 175  | mV                |
|                                                   |                       |              |                                                                       | -23 V ≤ V <sub>IN</sub> ≤ -11 V                                         | —    | 12   | 125  |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —    | 15   | 80   | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —    | 7.0  | 40   |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -23 V ≤ V <sub>IN</sub> ≤ -10.5 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -8.4 | —    | -7.6 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -8.4 | —    | -7.6 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —    | 3.1  | 6.5  | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                         | —    | —    | 6.0  |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -23 V ≤ V <sub>IN</sub> ≤ -11 V                                         | —    | —    | 1.5  | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —    | —    | 0.1  |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                            |                                                                         | —    | 60   | —    | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                         | —    | 20   | —    | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -23 V ≤ V <sub>IN</sub> ≤ -12 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 37   | 45   | —    | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —    | 1.7  | —    | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                         | —    | 0.8  | —    | mV/°C             |

**TA79L009P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -15\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                         | Min   | Typ. | Max   | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|-------|------|-------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | -9.36 | -9.0 | -8.64 | V                 |
| Line regulation                                   | Reg.line              | 1            | T <sub>j</sub> = 25°C                                                 | -24 V ≤ V <sub>IN</sub> ≤ -11.4 V                                       | —     | 80   | 200   | mV                |
|                                                   |                       |              |                                                                       | -24 V ≤ V <sub>IN</sub> ≤ -12 V                                         | —     | 20   | 160   |                   |
| Load regulation                                   | Reg.load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —     | 17   | 90    | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | 8.0  | 45    |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -24 V ≤ V <sub>IN</sub> ≤ -11.4 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -9.45 | —    | -8.55 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -9.45 | —    | -8.55 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 3.2  | 6.5   | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                         | —     | —    | 6.0   |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -24 V ≤ V <sub>IN</sub> ≤ -12 V                                         | —     | —    | 1.5   | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | —    | 0.1   |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | Ta = 25°C, 10 Hz ≤ f ≤ 100 kHz                                        |                                                                         | —     | 65   | —     | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                         | —     | 21   | —     | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -24 V ≤ V <sub>IN</sub> ≤ -12 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 36    | 44   | —     | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 1.7  | —     | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                         | —     | 0.85 | —     | mV/°C             |

**TA79L010P**
**Electrical Characteristics**

(Unless otherwise specified,  $V_{IN} = -16\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                         | Min   | Typ.  | Max  | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|-------|-------|------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | -10.4 | -10.0 | -9.6 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                 | -25 V ≤ V <sub>IN</sub> ≤ -12.5 V                                       | —     | 80    | 230  | mV                |
|                                                   |                       |              |                                                                       | -25 V ≤ V <sub>IN</sub> ≤ -13 V                                         | —     | 30    | 170  |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —     | 18    | 90   | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | 8.5   | 45   |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -25 V ≤ V <sub>IN</sub> ≤ -12.5 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -10.5 | —     | -9.5 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -10.5 | —     | -9.5 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 3.2   | 6.5  | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                         | —     | —     | 6.0  |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -25 V ≤ V <sub>IN</sub> ≤ -13 V                                         | —     | —     | 1.5  | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | —     | 0.1  |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                            |                                                                         | —     | 70    | —    | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                         | —     | 22    | —    | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -24 V ≤ V <sub>IN</sub> ≤ -13 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 36    | 43    | —    | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 1.7   | —    | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                         | —     | 0.9   | —    | mV/°C             |

**TA79L012P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -19\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                         | Min   | Typ.  | Max   | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|-------|-------|-------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | -12.5 | -12.0 | -11.5 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                 | -27 V ≤ V <sub>IN</sub> ≤ -14.5 V                                       | —     | 120   | 250   | mV                |
|                                                   |                       |              |                                                                       | -27 V ≤ V <sub>IN</sub> ≤ -16 V                                         | —     | 100   | 200   |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —     | 20    | 100   | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | 10    | 50    |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -27 V ≤ V <sub>IN</sub> ≤ -14.5 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -12.6 | —     | -11.4 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -12.6 | —     | -11.4 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 3.2   | 6.5   | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                         | —     | —     | 6.0   |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -27 V ≤ V <sub>IN</sub> ≤ -16 V                                         | —     | —     | 1.5   | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | —     | 0.1   |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | Ta = 25°C, 10 Hz ≤ f ≤ 100 kHz                                        |                                                                         | —     | 80    | —     | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                         | —     | 24    | —     | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -25 V ≤ V <sub>IN</sub> ≤ -15 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 37    | 42    | —     | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 1.7   | —     | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                         | —     | 1.0   | —     | mV/°C             |



**TA79L015P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -23\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                            |                                                                         | Min    | Typ.  | Max    | Unit              |
|---------------------------------------------------|-----------------------|--------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------|--------|-------|--------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                     |                                                                         | -15.6  | -15.0 | -14.4  | V                 |
| Line regulation                                   | Reg.line              | 1            | T <sub>j</sub> = 25°C                                                     | -30 V ≤ V <sub>IN</sub> ≤ -17.5 V                                       | —      | 130   | 300    | mV                |
|                                                   |                       |              |                                                                           | -30 V ≤ V <sub>IN</sub> ≤ -20 V                                         | —      | 110   | 250    |                   |
| Load regulation                                   | Reg.load              | 1            | T <sub>j</sub> = 25°C                                                     | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —      | 25    | 150    | mV                |
|                                                   |                       |              |                                                                           | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —      | 12    | 75     |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                     | -30 V ≤ V <sub>IN</sub> ≤ -17.5 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -15.75 | —     | -14.25 | V                 |
|                                                   |                       |              |                                                                           | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -15.75 | —     | -14.25 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                     |                                                                         | —      | 3.3   | 6.5    | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                    |                                                                         | —      | —     | 6.0    |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                     | -30 V ≤ V <sub>IN</sub> ≤ -20 V                                         | —      | —     | 1.5    | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                           | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —      | —     | 0.1    |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                                |                                                                         | —      | 90    | —      | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                         |                                                                         | —      | 30    | —      | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -28.5 V ≤ V <sub>IN</sub> ≤ -18.5 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 34     | 39    | —      | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                     |                                                                         | —      | 1.7   | —      | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                                   |                                                                         | —      | 1.3   | —      | mV/°C             |

**TA79L018P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -27\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                    | Test Circuit | Test Condition                                                                                                              | Min   | Typ.  | Max   | Unit                 |
|---------------------------------------------------|---------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------|-------|-------|-------|----------------------|
| Output voltage                                    | $V_{OUT}$                 | 1            | $T_j = 25^\circ\text{C}$                                                                                                    | -18.7 | -18.0 | -17.3 | V                    |
| Line regulation                                   | Reg.line                  | 1            | $T_j = 25^\circ\text{C}$ $-33\text{ V} \leq V_{IN} \leq 20.7\text{ V}$                                                      | —     | 32    | 325   | mV                   |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $-33\text{ V} \leq V_{IN} \leq -21\text{ V}$                                                       | —     | 27    | 275   |                      |
| Load regulation                                   | Reg.load                  | 1            | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 100\text{ mA}$                                                    | —     | 30    | 170   | mV                   |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$                                                     | —     | 15    | 75    |                      |
| Output voltage                                    | $V_{OUT}$                 | 1            | $T_j = 25^\circ\text{C}$ $-33\text{ V} \leq V_{IN} \leq -20.9\text{ V}$ ,<br>$1.0\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$ | -18.9 | —     | -17.1 | V                    |
|                                                   |                           |              | $T_j = 25^\circ\text{C}$ $1.0\text{ mA} \leq I_{OUT} \leq 70\text{ mA}$                                                     | -18.9 | —     | -17.1 |                      |
| Quiescent current                                 | $I_B$                     | 1            | $T_j = 25^\circ\text{C}$                                                                                                    | —     | 3.3   | 6.5   | mA                   |
|                                                   |                           |              | $T_j = 125^\circ\text{C}$                                                                                                   | —     | —     | 6.0   |                      |
| Quiescent current change                          | $\Delta I_{BI}$           | 1            | $T_j = 25^\circ\text{C}$ $-33\text{ V} \leq V_{IN} \leq -21\text{ V}$<br>$1.0\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$     | —     | —     | 1.5   | mA                   |
|                                                   | $\Delta I_{BO}$           | 1            |                                                                                                                             | —     | —     | 0.1   |                      |
| Output noise voltage                              | $V_{NO}$                  | 2            | $T_a = 25^\circ\text{C}$ , $10\text{ Hz} \leq f \leq 100\text{ kHz}$                                                        | —     | 150   | —     | $\mu\text{V}_{rms}$  |
| Long term stability                               | $\Delta V_{OUT}/\Delta t$ | 1            | —                                                                                                                           | —     | 45    | —     | mV/kh                |
| Ripple rejection ratio                            | R.R.                      | 3            | $-33\text{ V} \leq V_{IN} \leq -23\text{ V}$ ,<br>$T_j = 25^\circ\text{C}$ , $f = 120\text{ Hz}$                            | 33    | 48    | —     | dB                   |
| Dropout voltage                                   | $V_D$                     | 1            | $T_j = 25^\circ\text{C}$                                                                                                    | —     | 1.7   | —     | V                    |
| Average temperature coefficient of output voltage | $T_{CVO}$                 | 1            | $I_{OUT} = 5\text{ mA}$                                                                                                     | —     | 1.5   | —     | mV/ $^\circ\text{C}$ |

**TA79L020P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -29\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                         | Min   | Typ.  | Max   | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|-------|-------|-------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | -20.8 | -20.0 | -19.2 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                 | -35 V ≤ V <sub>IN</sub> ≤ -23.5 V                                       | —     | 33    | 330   | mV                |
|                                                   |                       |              |                                                                       | -35 V ≤ V <sub>IN</sub> ≤ -24 V                                         | —     | 28    | 285   |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                      | —     | 33    | 180   | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | 17    | 90    |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -35 V ≤ V <sub>IN</sub> ≤ -23.5 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -21.0 | —     | -19.0 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                       | -21.0 | —     | -19.0 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 3.3   | 6.5   | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                         | —     | —     | 6.0   |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -35 V ≤ V <sub>IN</sub> ≤ -24 V                                         | —     | —     | 1.5   | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                       | —     | —     | 0.1   |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                            |                                                                         | —     | 170   | —     | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                         | —     | 49    | —     | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -35 V ≤ V <sub>IN</sub> ≤ -27 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                         | 31    | 37    | —     | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                         | —     | 1.7   | —     | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                         | —     | 1.7   | —     | mV/°C             |


**TA79L024P**
**Electrical Characteristics**

 (Unless otherwise specified,  $V_{IN} = -33\text{ V}$ ,  $I_{OUT} = 40\text{ mA}$ ,  $C_{IN} = 0.33\text{ }\mu\text{F}$ ,  $C_{OUT} = 0.1\text{ }\mu\text{F}$ ,  $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ )

| Characteristics                                   | Symbol                | Test Circuit | Test Condition                                                        |                                                                       | Min   | Typ.  | Max   | Unit              |
|---------------------------------------------------|-----------------------|--------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-------|-------|-------|-------------------|
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 |                                                                       | -25.0 | -24.0 | -23.0 | V                 |
| Line regulation                                   | Reg-line              | 1            | T <sub>j</sub> = 25°C                                                 | -38 V ≤ V <sub>IN</sub> ≤ -27 V                                       | —     | 35    | 350   | mV                |
|                                                   |                       |              |                                                                       | -38 V ≤ V <sub>IN</sub> ≤ -28 V                                       | —     | 30    | 300   |                   |
| Load regulation                                   | Reg-load              | 1            | T <sub>j</sub> = 25°C                                                 | 1.0 mA ≤ I <sub>OUT</sub> ≤ 100 mA                                    | —     | 40    | 200   | mV                |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                     | —     | 20    | 100   |                   |
| Output voltage                                    | V <sub>OUT</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -38 V ≤ V <sub>IN</sub> ≤ -27 V,<br>1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA | -25.2 | —     | -22.8 | V                 |
|                                                   |                       |              |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 70 mA                                     | -25.2 | —     | -22.8 |                   |
| Quiescent current                                 | I <sub>B</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                       | —     | 3.5   | 6.5   | mA                |
|                                                   |                       |              | T <sub>j</sub> = 125°C                                                |                                                                       | —     | —     | 6.0   |                   |
| Quiescent current change                          | ΔI <sub>BI</sub>      | 1            | T <sub>j</sub> = 25°C                                                 | -38 V ≤ V <sub>IN</sub> ≤ -28 V                                       | —     | —     | 1.5   | mA                |
|                                                   | ΔI <sub>BO</sub>      | 1            |                                                                       | 1.0 mA ≤ I <sub>OUT</sub> ≤ 40 mA                                     | —     | —     | 0.1   |                   |
| Output noise voltage                              | V <sub>NO</sub>       | 2            | T <sub>a</sub> = 25°C, 10 Hz ≤ f ≤ 100 kHz                            |                                                                       | —     | 200   | —     | μV <sub>rms</sub> |
| Long term stability                               | ΔV <sub>OUT</sub> /Δt | 1            | —                                                                     |                                                                       | —     | 56    | —     | mV/kh             |
| Ripple rejection ratio                            | R.R.                  | 3            | -35 V ≤ V <sub>IN</sub> ≤ -29 V,<br>T <sub>j</sub> = 25°C, f = 120 Hz |                                                                       | 31    | 47    | —     | dB                |
| Dropout voltage                                   | V <sub>D</sub>        | 1            | T <sub>j</sub> = 25°C                                                 |                                                                       | —     | 1.7   | —     | V                 |
| Average temperature coefficient of output voltage | T <sub>CVO</sub>      | 1            | I <sub>OUT</sub> = 5 mA                                               |                                                                       | —     | 2.0   | —     | mV/°C             |


## Test Circuit 1

$V_{OUT}$ , Reg-line, Reg-load,  $I_B$ ,  $\Delta I_B$ ,  $\Delta V_{OUT}/\Delta t$ ,  $V_D$ ,  $T_{CVO}$




## Test Circuit 2






$V_{NO}$



## Test Circuit 3

R.R.






**Package Dimensions**

SSIP3-P-1.27

Unit : mm



Weight : 0.36 g (Typ.)

**RESTRICTIONS ON PRODUCT USE**

030619EBA

- The information contained herein is subject to change without notice.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.  
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.