

Centronic Sockets and Plugs

IDC for Flat Cables

Series: CBL_FB, CSL_FB

Features

- IDC technique for flat cables AWG28 (see note)
- 36 and 50 poles
- Female sockets encased with spring clips

Technical Specifications

Insulation Shell:	PBT Glass Filled, UL94V-0
Contact Material:	Phosphor Bronze
Contact Surface:	Gold Over Nickel
Housing:	Steel
Operating Current:	5A
Contact Resistance (For 1 Min.):	1000V AC
Isolation Resistance (at 500V DC), Min.:	1000MΩ
Temperature Range:	-55...+105°C

Dimensions

Part Nr.	Nr. of Poles	A [mm]	B [mm]	C [mm]
CBL36FB	36	36,72	61,60	53,30
CBL50FB	50	51,84	82,80	68,50
CSL36FB	36	36,72	61,60	53,30
CSL50FB	50	51,84	76,70	68,50

Note

- You will find suitable flat cables in product groups G1833 and G1837
- For suitable IDC crimping fixtures, please see product group T4651 in our "Components and Devices" catalogue.

Terms of Delivery

Minimum order quantity: 1 PKU = 5 pieces

Manufacturer: Various

Part Nr.	Part description
CBL36FB	Centronics Socket 36-Pole
CBL50FB	Centronics Socket 50-Pole
CSL36FB	Centronics Plug 36-Pole
CSL50FB	Centronics Plug 50-Pole

