


Ring Terminals

SPECIFICATION

Electrolytic Copper
Tin Plated
Easy Entry
P.V.C. Insulation




| Part No. | $\phi d2$ | B | L | F | H | ϕD | Wire Size AWG(mm ²) | Current Rating | Insulation Color | Qty/Box | Weight/ Box | | | | | |
|------------|-----------|------|------|------|------|----------|------------------------------------|-------------------|---------------------|---------|----------------|----------------------|-----|------|------|-------|
| KTL-001-01 | 3.2 | 5.5 | 16.5 | 4.3 | 9.5 | 3.5 | 22~20 (0.25~1.0) | 10A | Red | 3000 | 1.2kg | | | | | |
| KTL-001-02 | 4.3 | 8.0 | 20.0 | 6.6 | | | | | | 3000 | 1.6kg | | | | | |
| KTL-001-03 | 5.3 | 8.0 | 20.0 | 6.6 | | | | | | 3000 | 1.6kg | | | | | |
| KTL-001-04 | 3.2 | 5.5 | 18.0 | 4.3 | 11.0 | 4.0 | 22~16 (0.25~1.65) | 19A | Red | 3000 | 1.8kg | | | | | |
| KTL-001-05 | 3.7 | 5.5 | 18.0 | 4.3 | | | | | | 3000 | 1.7kg | | | | | |
| KTL-001-06 | 3.2 | 6.6 | 20.9 | 6.6 | | | | | | 3000 | 2.0kg | | | | | |
| KTL-001-07 | 3.7 | 6.6 | 20.9 | 6.6 | | | | | | 3000 | 2.1kg | | | | | |
| KTL-001-08 | 4.3 | 8.0 | 22.3 | 7.3 | | | | | | 3000 | 2.3kg | | | | | |
| KTL-001-09 | 4.3 | 6.6 | 20.9 | 6.6 | | | | | | 3000 | 2.0kg | | | | | |
| KTL-001-10 | 5.3 | 8.0 | 22.3 | 7.3 | | | | | | 3000 | 2.2kg | | | | | |
| KTL-001-11 | 6.4 | 11.6 | 28.2 | 11.4 | | | | | | 2000 | 2.3kg | | | | | |
| KTL-001-12 | 8.4 | 11.6 | 28.2 | 11.4 | | | | | | 2000 | 1.9kg | | | | | |
| KTL-001-13 | 3.2 | 8.5 | 23.0 | 7.75 | | | | | | 11.0 | 4.5 | 16~14 (1.04~2.63) | 27A | Blue | 2000 | 2.0kg |
| KTL-001-14 | 3.7 | 6.6 | 20.6 | 6.3 | 2000 | 1.9kg | | | | | | | | | | |
| KTL-001-15 | 4.3 | 8.5 | 23.0 | 7.75 | 2000 | 2.0kg | | | | | | | | | | |
| KTL-001-16 | 4.3 | 6.6 | 20.6 | 6.3 | 2000 | 1.6kg | | | | | | | | | | |
| KTL-001-17 | 5.3 | 9.5 | 23.0 | 7.25 | 2000 | 2.0kg | | | | | | | | | | |
| KTL-001-18 | 6.4 | 12.0 | 28.0 | 11.0 | 2000 | 2.7kg | | | | | | | | | | |
| KTL-001-19 | 8.4 | 12.0 | 28.0 | 11.0 | 2000 | 2.6kg | | | | | | | | | | |
| KTL-001-20 | 10.5 | 13.6 | 31.7 | 13.9 | 1500 | 1.8kg | | | | | | | | | | |
| KTL-001-21 | 4.3 | 9.5 | 26.9 | 8.2 | 13.7 | 6.3 | 12~10 (2.63~4.6) | 37A | Yellow | | | | | | 1500 | 2.0kg |
| KTL-001-22 | 5.3 | 9.5 | 26.9 | 8.2 | | | | | | | | | | | 1500 | 2.2kg |
| KTL-001-23 | 6.4 | 12.0 | 28.3 | 8.5 | | | | | | 1500 | 2.5kg | | | | | |
| KTL-001-24 | 3.7 | 9.5 | 26.7 | 8.25 | 13.7 | 6.3 | 12~10 (2.63~6.64) | 48A | Yellow | 1500 | 3.1kg | | | | | |
| KTL-001-25 | 4.3 | 9.5 | 26.7 | 8.25 | | | | | | 1500 | 2.9kg | | | | | |
| KTL-001-26 | 5.3 | 9.5 | 26.7 | 8.25 | | | | | | 1500 | 2.8kg | | | | | |
| KTL-001-27 | 6.4 | 12.0 | 32.7 | 13.0 | | | | | | 1500 | 2.5kg | | | | | |
| KTL-001-28 | 8.4 | 15.0 | 34.9 | 13.7 | | | | | | 1500 | 4.0kg | | | | | |
| KTL-001-29 | 10.5 | 15.0 | 34.9 | 13.7 | | | | | | 1500 | 3.7kg | | | | | |

Fork Terminals

SPECIFICATION

Electrolytic Copper
Tin Plated
Easy Entry
P.V.C. Insulation



| Part No. | $\phi d2$ | B | L | F | H | ϕD | Wire Size AWG(mm ²) | Current Rating | Insulation Color | Qty/Box | Weight/ Box |
|------------|-----------|------|------|------|------|----------|------------------------------------|-------------------|---------------------|---------|----------------|
| KTL-002-01 | 3.2 | 5.7 | 22.5 | 6.5 | 11.0 | 4.0 | 22~16 (0.25~1.65) | 19A | Red | 3000 | 2.2kg |
| KTL-002-02 | 3.7 | 5.7 | 22.5 | 6.5 | | | | | | 3000 | 2.0kg |
| KTL-002-03 | 3.7 | 6.2 | 22.5 | 6.5 | | | | | | 3000 | 2.1kg |
| KTL-002-04 | 4.3 | 6.4 | 22.5 | 6.5 | | | | | | 3000 | 2.1kg |
| KTL-002-05 | 4.3 | 7.2 | 22.5 | 6.5 | | | | | | 3000 | 2.2kg |
| KTL-002-06 | 5.3 | 8.0 | 22.5 | 6.5 | | | | | | 3000 | 2.2kg |
| KTL-002-07 | 3.2 | 5.7 | 22.5 | 6.5 | 11.0 | 4.5 | 16~14 (1.04~2.63) | 27A | Blue | 2000 | 1.7kg |
| KTL-002-08 | 3.7 | 5.7 | 22.5 | 6.5 | | | | | | 2000 | 1.6kg |
| KTL-002-09 | 3.7 | 6.2 | 22.5 | 6.5 | | | | | | 2000 | 1.7kg |
| KTL-002-10 | 4.3 | 6.4 | 22.5 | 6.5 | | | | | | 2000 | 1.7kg |
| KTL-002-11 | 4.3 | 7.2 | 22.5 | 6.5 | | | | | | 2000 | 1.8kg |
| KTL-002-12 | 5.3 | 8.0 | 22.5 | 6.5 | | | | | | 2000 | 1.7kg |
| KTL-002-13 | 6.4 | 10.7 | 25.5 | 9.0 | 13.7 | 6.3 | 12~10 (2.63~4.62) | 37A | Yellow | 2000 | 2.3kg |
| KTL-002-14 | 4.3 | 8.0 | 25.4 | 6.9 | | | | | | 1500 | 2.0kg |
| KTL-002-15 | 5.3 | 8.0 | 25.4 | 8.0 | 13.7 | 6.3 | 12~10 (2.63~6.64) | 48A | Yellow | 1500 | 2.2kg |
| KTL-002-16 | 3.2 | 7.3 | 26.7 | 7.1 | | | | | | 1500 | 2.7kg |
| KTL-002-17 | 3.7 | 8.2 | 26.7 | 7.5 | | | | | | 1500 | 2.3kg |
| KTL-002-18 | 4.3 | 8.2 | 26.7 | 7.5 | | | | | | 1000 | 1.9kg |
| KTL-002-19 | 5.3 | 9.0 | 26.7 | 8.0 | | | | | | 1000 | 1.9kg |
| KTL-002-20 | 6.4 | 12.0 | 32.7 | 12.0 | | | | | | 1000 | 2.5kg |