


Item no.: 233-202
 Product description: PCB TERMINAL STRIP 2 SOLDER PINS / POLE 2 POLE PIN
 SPACING 2.5 MM / 0.098 IN WITH PUSH BUTTONS FRONT-
 ENTRY CAGE CLAMP®CONNECTION



Packing unit 600 6*100 pieces

Product group	4 (Printed Circuit)
Pin spacing from	2,5 mm
Pin spacing from	0,098 in
pole count	2
Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	0,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	20 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	2,5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	0,893 g
Color	grey
Wiring type	Angled Type
No. of connection Points	2
No. of potentials	2
Height	15,5 mm
Height	0,61 in
Width	7,3 mm
Width	0,287 in



Depth	13,9 mm
Depth	0,547 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0,22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
233-202	ABS	04-HG469925-PDA	250	4	0,8-0,5
233-202	BV	11915/A0	250	6	0,08-0,5
233-202	CSA	154112-1465035	150	4	28-20
233-202	DEMKO	118980ES	250	4	0,5
233-202	DEMKO	DK96-03660	250	4	0,8-0,5
233-202	DNV	E7569	250	4	0,8-0,5
233-202	GL	17296-00HH	250	4	0,8-0,5
233-202	KEMA	90.6212.01/02	250	6	0,08-0,5
233-202	RMR	11130002	250	4	0,8-0,5
233-202	SEMKO	9043004	250		0,5
233-202	UR	E45172	150	7	18-28

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected