



Products for tomorrow

Headquarter Europe
 MEDER electronic AG
 Friedrich-List Strasse 6
 D-78234 Engen-Welschingen
 Tel.: +49(0)7733-9487-0
 Fax: +49(0)7733-9487-32
 eMail: info@meder.com
 Internet: www.meder.com

Headquarter USA
 MEDER electronic Inc.
 766 Falmouth Rd
 Mashpee, MA 02649
 Phone: +1/ 508-539-0002
 Fax: +1/ 508-539-4088
 eMail: salesusa@meder.com




Reed Relay: MS05-1A87-75D

Part Number: 4205187175

Dimensions (mm) Unspecified Tolerances +/- 0.10mm

Layout / Pitch 3.81 mm / Top View

Marking



Coil/Relay Characteristics	Conditions at 20°C	Min.	Typ.	Max.	Units
Coil Resistance		252	280	308	Ω
Nominal Voltage			5.0		VDC
Nominal Rated Power			90		mW
Operate Voltage				3.75	VDC
Release Voltage		0.75			VDC

Contact Data 87 (Form A/Dry)					
Contact Rating	Any combination of the switching voltage and current must not exceed the given rated power			10	W
Switching Voltage	DC or Peak AC			200	V
Switching Current	DC or Peak AC			0.5	A
Carry Current	DC or Peak AC			1.0	A
Static Contact Resistance (initial)	Measured with Nominal Voltage			150	mΩ
Insulation Resistance	RH 45%	10 ¹¹	10 ¹²		Ω
Breakdown Voltage		225			VDC
Operate Time, including Bounce	Measured with Nominal Voltage			0.5	ms
Release Time	Measured with no coil suppression			0.1	ms
Capacitance			0.2		pF

Environmental Data					
Insulation Resistance Coil to Contact	RH 45%	10 ¹³	10 ¹⁴		Ω
Dielectric Strength Coil to Contact		1.5			kV DC
Shock	½ sine wave, duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating Temperature	10°C/min max. allowable	-20		+70	°C
Storage Temperature	10°C/min max. allowable	-35		+95	°C
Soldering Temperature	5 sec. at			260	°C
Cleaning					fully sealed
Material of Case					mineral filled epoxy
Material of Pins					FeNi-alloy tinned
Remarks					

Customer / Customer part number	
---------------------------------	--