



2P~6P 增加防脫卡點

2P~6P

>6P

P	2	3	4	5	6	7	8	9	10	11	12	13
U	3.50	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50	42.00
V	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50	42.00	45.50
P	14	15	16	17	18	19	20	21	22	23	24	
U	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50	
V	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50	84.00	
Tolerances for PITCH ERROR												

NOTES:

- Rating: 300V 8A (IEC 125V 12A)
PITCH: 3.50mm
- Insulation Withstands Voltage:
AC 2000V/MIN
- Insulation Resistance:
1000MΩ or more at DC500V
- Using Temperature Range:
-40°C~+110°C
- Suitable Electric Wire: AWG 28~16 (1.5mm²)
- Screw Torque Value: 2kgf-cm
- Undimensioned Tolerances:

\pm	\square	∇	0.05/10
\perp	\parallel	\equiv	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONS TOLERANCES			±0.3

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

5	SOLDER PIN	P	BRONZE	TIN Plated
4	SCREW	P	STEEL	M2/Zn Plated
3	COVER	1	PBT	GREEN
2	WIRE CAGE	P	Hard Brass	M2/Ni Plated

APPD. 核准	Judie	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 3.5mm TERMINAL BLOCK STRAIGHT H=15.5mm 16-28AWG NI PLATED ROHS LOW-LAED
DWG. 製圖	Jolin		
DATE 制表日	2007/04/10	SCALE 比例 參考	PART NO. 料號 C0916-XXNFNX00R
		UNIT 單位 MM	
		PAGE 張數 1 / 1	
		REV. 版次 A	