

BUFFERS/DRIVERS

54/74365A, 366A, 367A, 368A, LS365A, LS366A, LS367A, LS368A

**'365A, '367A Hex Buffer/Driver (3-State)
'366A, '368A Hex Inverter Buffer (3-State)**

TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT (Total)
74365A, 367A	10ns	65mA
74LS365A, 367A	10ns	14mA
74366A, 368A	9ns	59mA
74LS366A, 368A	10ns	12mA

ORDERING CODE

PACKAGES	COMMERCIAL RANGES	MILITARY RANGES
	$V_{CC} = 5V \pm 5\%$; $T_A = 0^\circ C$ to $+70^\circ C$	$V_{CC} = 5V \pm 10\%$; $T_A = -55^\circ C$ to $+125^\circ C$
Plastic DIP	N74365AN • N74LS365AN N74366AN • N74LS366AN N74367AN • N74LS367AN N74368AN • N74LS368AN	
Plastic SO	N74LS365AD • N74LS367AD N74LS368AD	
Ceramic DIP		S54365AF • S54LS365AF S54366AF • S54LS366AF S54367AF • S54LS367AF S54368AF • S54LS368AF
Flatpack		S54365AW • S54LS365AW S54366AW • S54LS366AW S54367AW • S54LS367AW S54368AW • S54LS368AW
LLCC		S54LS365AG S54LS367AG

FUNCTION TABLE, '365A, '366A

INPUTS			OUTPUTS	
\overline{OE}_1	\overline{OE}_2	I	Y	\overline{Y}
L	L	L	L	H
L	L	H	H	L
X	H	X	(Z)	(Z)
H	X	X	(Z)	(Z)

FUNCTION TABLE, '367A, '368A

INPUTS		OUTPUTS	
\overline{OE}	I	Y	\overline{Y}
L	L	L	H
L	H	H	L
H	X	(Z)	(Z)


L = LOW voltage level
H = HIGH voltage level
X = Don't care
(Z) = HIGH impedance (off) state

INPUT AND OUTPUT LOADING AND FAN-OUT TABLE

PINS	DESCRIPTION	54/74	54/74LS
All	Inputs	1uI	1LSuI
All	Outputs	20uI	30LSuI

NOTE
Where a 54/74 unit load (uI) is understood to be 40 μ A I_{IH} and - 1.6mA I_{IL} and a 54/74LS unit load (LSuI) is 20 μ A I_{IH} and - 0.4mA I_{IL}


PIN CONFIGURATION




BUFFERS/DRIVERS

54/74365A, 366A, 367A, 368A, LS365A, LS366A, LS367A, LS368A

LOGIC SYMBOL



LOGIC SYMBOL (IEEE/IEC)



ABSOLUTE MAXIMUM RATINGS (Over operating free-air temperature range unless otherwise noted.)

PARAMETER	54	54LS	74	74LS	UNIT
V _{CC} Supply voltage	7.0	7.0	7.0	7.0	V
V _{IN} Input voltage	-0.5 to +5.5	-0.5 to +7.0	-0.5 to +5.5	-0.5 to +7.0	V
I _{IN} Input current	-30 to +5	-30 to +1	-30 to +5	-30 to +1	mA
V _{OUT} Voltage applied to output in HIGH output state	-0.5 to +V _{CC}	V			
T _A Operating free-air temperature range	-55 to +125		0 to 70		°C

RECOMMENDED OPERATING CONDITIONS

PARAMETER		54/74			54/74LS			UNIT	
		Min	Nom	Max	Min	Nom	Max		
V _{CC}	Supply voltage	Min	4.5	5.0	5.5	4.5	5.0	5.5	V
		Com'l	4.75	5.0	5.25	4.75	5.0	5.25	V
V _{IH}	HIGH-level input voltage	2.0			2.0			V	
V _{IL}	LOW-level input voltage	Min		+0.8			+0.7	V	
		Com'l		+0.8			+0.8	V	
I _{IK}	Input clamp current			-12			-18	mA	
I _{OH}	HIGH-level output current	Min		-2.0			-1.0	mA	
		Com'l		-5.2			-2.6	mA	
I _{OL}	LOW-level output current	Min		32			12	mA	
		Com'l		32			24	mA	
T _A	Operating free-air temperature	Min	-55	+125	-55		+125	°C	
		Com'l	0	70	0		70	°C	

TEST CIRCUITS AND WAVEFORMS

TEST CIRCUIT FOR 3-STATE OUTPUTS

SWITCH POSITION

Test	Switch 1	Switch 2
t _{pZH}	Open	Closed
t _{pZL}	Closed	Open
t _{pHZ}	Closed	Closed
t _{pLZ}	Closed	Closed

DEFINITIONS
 R_L = Load resistor to V_{CC}; see AC CHARACTERISTICS for value.
 C_L = Load capacitance includes jig and probe capacitance; see AC CHARACTERISTICS for value.
 R_T = Termination resistance should be equal to Z_{OUT} of Pulse Generators.
 D = Diodes are 1N916, 1N3064, or equivalent.
 R_X = 1kΩ for 54/74, 54S/74S, R_X = 5kΩ for 54LS/74LS.
 t_{TLH}, t_{THL} Values should be less than or equal to the table entries.

INPUT PULSE DEFINITIONS

V_M = 1.3V for 54LS/74LS; V_M = 1.5V for all other TTL families.

FAMILY	INPUT PULSE REQUIREMENTS				
	Amplitude	Rep. Rate	Pulse Width	t _{TLH}	t _{THL}
54/74	3.0V	1MHz	500ns	7ns	7ns
54LS/74LS	3.0V	1MHz	500ns	15ns	6ns
54S/74S	3.0V	1MHz	500ns	2.5ns	2.5ns

BUFFERS/DRIVERS

54/74365A, 366A, 367A, 368A, LS365A, LS366A, LS367A, LS368A

DC ELECTRICAL CHARACTERISTICS (Over recommended operating free-air temperature range unless otherwise noted.)

PARAMETER	TEST CONDITIONS ¹	54/74365A, '366A, '367A, '368A			54/74LS365A, '366A, '367A, '368A			UNIT
		Min	Typ ²	Max	Min	Typ ²	Max	
V _{OH} HIGH-level output voltage	V _{CC} = MIN, V _{IH} = MIN, V _{IL} = MAX, I _{OH} = MAX	Mil	2.4	3.3		2.4	3.3	V
		Com'l	2.4	3.1		2.4	3.1	V
V _{OL} LOW-level output voltage	V _{CC} = MIN, V _{IH} = MIN, V _{IL} = MAX	I _{OL} = MAX			0.4	0.25	0.4	V
			Com'l		0.4	0.35	0.5	V
		I _{OL} = 12mA	74LS			0.25	0.4	V
V _{IK} Input clamp voltage	V _{CC} = MIN, I _I = I _{IK}				-1.5		-1.5	V
I _{OZH} Off-state output current, HIGH-level voltage applied	V _{CC} = MAX, V _{IH} = MIN, V _{IL} = MAX, V _O = 2.4V				40		20	μA
I _{OZL} Off-state output current, LOW-level voltage applied	V _{CC} = MAX, V _{IH} = MIN, V _{IL} = MAX, V _O = 0.4V				-40		-20	μA
I _I Input current at maximum input voltage	V _{CC} = MAX	V _I = 5.5V			1.0			mA
		V _I = 7.0V					0.1	mA
I _{IH} HIGH-level input current	V _{CC} = MAX	V _I = 2.4V			40			μA
		V _I = 2.7V					20	μA
I _{IL} LOW-level input current	V _{CC} = MAX	1 inputs, V _I = 0.5V Either \overline{OE} input at 2.0V Does not apply to 'LS365A or 'LS367A			-40		-20	μA
		1 inputs V _I = 0.4V Both \overline{OE} inputs at 0.4V			-1.6		-0.4	mA
		\overline{OE} inputs V _I = 0.4V			-1.6		-0.4	mA
I _{OS} Short-circuit output current ³	V _{CC} = MAX		-40		-130		-130	mA
I _{CC} Supply current ⁴ (total)	V _{CC} = MAX	'365A, '367A		65	85	14	24	mA
		'366A, '368A		59	77	12	21	mA

NOTES


- For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
- All typical values are at V_{CC} = 5V, T_A = 25°C.
- I_{OS} is tested with V_{OUT} = +0.5V and V_{CC} = V_{CC} MAX + 0.5V. Not more than one output should be shorted at a time and duration of the short circuit should not exceed one second.
- Measure I_{CC} with Data inputs grounded and Output Enable Inputs at 4.5V.

AC CHARACTERISTICS T_A = 25°C, V_{CC} = 5.0V

PARAMETER	TEST CONDITIONS	54/74		54LS/74LS		UNIT
		C _L = 50pF, R _L = 400Ω		C _L = 45pF, R _L = 667Ω		
		Min	Max	Min	Max	
t _{PLH} t _{PHL} Propagation delay	Waveform 1, '366A, '368A		17 16		15 18	ns
t _{PLH} t _{PHL} Propagation delay	Waveform 2, '365A, '367A		16 22		16 22	ns
t _{PZH} Enable to HIGH	Waveform 3		35		35	ns
t _{PZL} Enable to LOW	Waveform 4	'365A, '367A	37		40	ns
		'366A, '368A	37		45	ns
t _{PHZ} Disable from HIGH	Waveform 3, C _L = 5pF	'365A, '367A	11		30	ns
		'366A, '368A	11		32	ns
t _{PLZ} Disable from LOW	Waveform 4, C _L = 5pF		27		35	ns


AC WAVEFORMS

WAVEFORM FOR INVERTING OUTPUTS




Waveform 1

WAVEFORM FOR NON-INVERTING OUTPUTS




Waveform 2

3-STATE ENABLE TIME TO HIGH LEVEL AND DISABLE TIME FROM HIGH LEVEL



Waveform 3

3-STATE ENABLE TIME TO LOW LEVEL AND DISABLE TIME FROM LOW LEVEL



Waveform 4

$V_M = 1.3V$ for 54LS/74LS, $V_M = 1.5V$ for all other TTL families.